


NYMPHEA 2 TOP 18W plafond




Power	18 W	Voltage	230 V
Luminous flux*	1600 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	120 °
IK	10	Degree of protection (IP)	IP44




See more on dedicated page 



 Declaration of Conformity



 Photometric file

Technical data:

Code	SLI031030NW
Power	18 W
Nominal current	150 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	18 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	1600 lm (120°)
Luminous flux**	1600 lm (360°)
Lamp efficacy	88 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	10
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	330x60 mm
Weight	1.012 kg
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC



*applies to the LED source used. **Luminaire luminous flux
For request available version with motion sensor (SLI031030NW_CZUJNIK).