


## ALGINE LINE 44W led panel




Power	<b>44 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5300 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Colour of light	<b>Neutral white</b>	Beam angle	<b>70 °</b>
UGR	<b>&lt;16</b>	IK	<b>06</b>



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

**Technical data:**

Code	SLI035050NW
Power	44 W
Nominal current	200 mA
Voltage	230 V
Energy efficiency class	C
Energy consumption	44 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Manufacturer of power supply	PHILIPS
Power factor	0,9
Useful luminous flux*	5300 lm (360°)
Luminous flux**	5300 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	70 °
UGR	<16
RA	80
Producer of LED diodes	PHILIPS
Uniformity of color SDCM max	5
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	STEEL
IK	06
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	597x597x40 mm
Mounting hole	565x565 mm
Weight	3.18 kg
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



\*applies to the LED source used. \*\*Luminaire luminous flux  
Also available as DALI, DIM, DIMRF.