

PAVA



Power **35 W**
Colour temperature **3000 K**
Degree of protection (IP) **IP20**

Voltage **230 V**
Colour of light **WW**



See more on dedicated page 



 Declaration of Conformity




 Photometric file

MDR37PRO35930RB

Technical data:

Code	WOJP00384
Power	35 W
Nominal current	167.4 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	3850 lm (360°)
Luminous flux**	3500 lm (360°)
Lamp efficacy	110 lm/W
Colour temperature	3000 K
Colour of light	WW
RA	90
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	102x176x184 mm
Weight	1.79 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL



*applies to the LED source used. **Luminaire luminous flux