

Product Environmental Profile

RP Series Expansion Remote Control RP-C-RC-BLE






General information

Representative product	RP Series Expansion Remote Control RP-C-RC-BLE - SXWRERCBLE10001
Description of the product	The RP-C-RC-BLE Remote Control enables the occupants of modern office buildings to control the comfort level of their space.
Functional unit	To control lights, blinds, temperature setpoint and fan speed, using Bluetooth Low Energy wireless communication protocol and pairs with the multi-sensor in the room, with maximum communication distance of 50 m line-of-sight, during 10 years, powered by battery.



Constituent materials

Reference product mass 121 g including the product, its packaging and additional elements and accessories



Plastics	45.3%
Metals	0.5%
Others	54.2%



Substance assessment

Products of this range are designed in conformity with the requirements of the RoHS directive (European Directive 2011/65/EU of 8 June 2011) and do not contain, or only contain in the authorised proportions, lead, mercury, cadmium, hexavalent chromium or flame retardants (polybrominated biphenyls - PBB, polybrominated diphenyl ethers - PBDE) as mentioned in the Directive

Details of ROHS and REACH substances information are available on the Schneider-Electric Green Premium website

<http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page>

Additional environmental information


The RP Series Expansion Remote Control RP-C-RC-BLE presents the following relevant environmental aspects

Manufacturing	Manufactured at a Schneider Electric production site ISO14001 certified
Distribution	Weight and volume of the packaging optimized, based on the European Union's packaging directive Packaging weight is 16 g, consisting of cardboard (81%), paper (19%) Packaging recycled materials is 60% of total packaging mass. Product distribution optimised by setting up local distribution centres
Installation	Ref SXWRERCBLE10001 does not require any installation operations.
Use	1 battery of 6g have to be changed every five years.
End of life	End of life optimized to decrease the amount of waste and allow recovery of the product components and materials This product contains electronic card (19g), LCD module (14g) and battery (6g) that should be separated from the stream of waste so as to optimize end-of-life treatment. The location of these components and other recommendations are given in the End of Life Instruction document which is available on the Schneider-Electric Green Premium website http://www2.schneider-electric.com/sites/corporate/en/products-services/green-premium/green-premium.page Recyclability potential: 56% Based on "ECO'DEEE recyclability and recoverability calculation method" (version V1, 20 Sep. 2008 presented to the French Agency for Environment and Energy Management: ADEME).

Environmental impacts

Reference life time	10 years		
Product category	Other equipments - Active product		
Installation elements	Disposal of packaging is accounted for in the installation phase.		
Use scenario	Remote Control with internal battery and a life time of 10 years. Battery life is 5 years and one replacement is accounted for in LCA.		
Geographical representativeness	Europe		
Technological representativeness	The RP-C-RC-BLE Remote Control enables the occupants of modern office buildings to control the comfort level of their space.		
Energy model used	Manufacturing	Installation	Use
	Energy model used: Romania	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27	Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27
			End of life Electricity grid mix; AC; consumption mix, at consumer; < 1kV; EU-27

Compulsory indicators		RP Series Expansion Remote Control RP-C-RC-BLE - SXWRERCBLE10001					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to mineral resources depletion	kg Sb eq	3.72E-04	3.69E-04	0*	0*	2.88E-06	0*
Contribution to the soil and water acidification	kg SO ₂ eq	2.17E-02	2.15E-02	7.13E-05	3.61E-06	7.39E-05	5.22E-05
Contribution to water eutrophication	kg PO ₄ ³⁻ eq	8.52E-03	8.47E-03	1.64E-05	8.77E-07	1.18E-05	2.13E-05
Contribution to global warming	kg CO ₂ eq	1.86E+01	1.85E+01	1.56E-02	0*	2.46E-02	5.97E-02
Contribution to ozone layer depletion	kg CFC11 eq	6.06E-07	5.99E-07	0*	0*	4.65E-09	2.75E-09
Contribution to photochemical oxidation	kg C ₂ H ₄ eq	2.24E-03	2.23E-03	5.09E-06	2.70E-07	4.83E-06	4.93E-06
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Net use of freshwater	m ³	1.82E-01	1.82E-01	0*	0*	4.63E-04	4.03E-05
Total Primary Energy	MJ	2.90E+02	2.89E+02	2.21E-01	0*	4.62E-01	2.53E-01




Optional indicators		RP Series Expansion Remote Control RP-C-RC-BLE - SXWRERCBLE10001					
Impact indicators	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Contribution to fossil resources depletion	MJ	2.77E+02	2.76E+02	2.19E-01	0*	3.03E-01	1.97E-01
Contribution to air pollution	m³	1.86E+03	1.85E+03	6.64E-01	0*	7.66E+00	2.03E+00
Contribution to water pollution	m³	1.14E+03	1.13E+03	2.57E+00	1.31E-01	1.22E+00	2.91E+00
Resources use	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Use of secondary material	kg	1.21E-02	1.21E-02	0*	0*	0*	0*
Total use of renewable primary energy resources	MJ	1.46E+00	1.46E+00	2.94E-04	0*	6.70E-04	2.33E-04
Total use of non-renewable primary energy resources	MJ	2.89E+02	2.88E+02	2.20E-01	0*	4.61E-01	2.52E-01
Use of renewable primary energy excluding renewable primary energy used as raw material	MJ	1.42E+00	1.42E+00	2.94E-04	0*	6.70E-04	2.33E-04
Use of renewable primary energy resources used as raw material	MJ	4.24E-02	4.24E-02	0*	0*	0*	0*
Use of non renewable primary energy excluding non renewable primary energy used as raw material	MJ	2.86E+02	2.85E+02	2.20E-01	0*	4.51E-01	2.52E-01
Use of non renewable primary energy resources used as raw material	MJ	2.47E+00	2.46E+00	0*	0*	1.00E-02	0*
Use of non renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Use of renewable secondary fuels	MJ	0.00E+00	0*	0*	0*	0*	0*
Waste categories	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Hazardous waste disposed	kg	1.42E+00	1.22E+00	0*	0*	5.29E-04	1.93E-01
Non hazardous waste disposed	kg	3.73E+00	3.72E+00	5.55E-04	0*	8.24E-04	2.46E-03
Radioactive waste disposed	kg	6.09E-04	6.06E-04	3.95E-07	0*	5.64E-07	1.62E-06
Other environmental information	Unit	Total	Manufacturing	Distribution	Installation	Use	End of Life
Materials for recycling	kg	8.10E-02	6.97E-03	0*	1.59E-02	0*	5.81E-02
Components for reuse	kg	0.00E+00	0*	0*	0*	0*	0*
Materials for energy recovery	kg	1.43E-02	0*	0*	0*	0*	1.43E-02
Exported Energy	MJ	5.04E-05	4.61E-06	0*	4.58E-05	0*	0*

* represents less than 0.01% of the total life cycle of the reference flow

Life cycle assessment performed with EIME version EIME v5.8.1, database version 2016-11 in compliance with ISO14044.

The manufacturing phase is the life cycle phase which has the greatest impact on the majority of environmental indicators (based on compulsory indicators).

Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

<i>Registration number :</i>	SCHN-00613-V01.01-EN	<i>Drafting rules</i>	PCR-ed3-EN-2015 04 02
<i>Verifier accreditation N°</i>	VH30	<i>Supplemented by</i>	PSR-0005-ed2-EN-2016 03 29
<i>Date of issue</i>	09/2020	<i>Information and reference documents</i>	www.pep-ecopassport.org
		<i>Validity period</i>	5 years
<i>Independent verification of the declaration and data, in compliance with ISO 14025 : 2010</i>			
Internal	X	External	
<i>The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)</i>			
<i>PEP are compliant with XP C08-100-1 :2016</i>			
<i>The elements of the present PEP cannot be compared with elements from another program.</i>			
<i>Document in compliance with ISO 14025 : 2010 « Environmental labels and declarations. Type III environmental declarations »</i>			
			

Schneider Electric Industries SAS

Country Customer Care Center

<http://www.schneider-electric.com/contact>

35, rue Joseph Monier

CS 30323

F- 92506 Rueil Malmaison Cedex

RCS Nanterre 954 503 439

Capital social 896 313 776 €

www.schneider-electric.com

Published by Schneider Electric

SCHN-00613-V01.01-EN

© 2019 - Schneider Electric – All rights reserved

09/2020