

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Portable socket-outlet Rewirable portable socket-outlets
Name and address of the applicant	LEGRAND FRANCE 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE
Name and address of the manufacturer	LEGRAND FRANCE 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE
Name and address of the factory	NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD East Industrial Zone, 315314 Guanhaiwei Cixi City Zhejiang Province - CHINA
Note: When more than one factory, please report on page 2	<input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	See Annex
Trademark / Brand (if any)	legrand
Customer's Testing Facility (CTF) Stage used	/
Model / Type Ref.	See Annex
Additional information (if necessary may also be reported on page 2)	Supersedes CBTC FR_708385 dated 27/04/2020. Update further to the evolution of the standard(s) Update the list of components <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60884-1:2002(ed.3) +A1:2006 +A2:2013
As shown in the Test Report Ref. No. which forms part of this Certificate	ABND-ESH-P21032612

This CB Test Certificate is issued by the National Certification Body



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 25/06/2021

Signature:  **Jérôme REYSSON**
Certification Officer



ANNEX

References, ratings and main characteristics:

Model	Type Reference	Number of socket-outlets	Color of enclosure
RNS10X	0 494 96	3	white/grey
	0 494 97	4	white/grey
	0 494 98	5	white/grey
	0 494 99	6	white/grey

standard Sheet:	Standard Sheet V of CEE 7
rated current (A)	16A
rated load (W)	3680W
rated voltage (V)	250V
household voltage (V)	230V
degree of protection	IP20
provision for earthing	with earthing contact (with solid earthing pin or non-solid earthing pin)
method of connecting the cable	rewirable
type of terminals	screw-type
type of connections	-
colour	white/grey
socket-outlets	
multiple socket-outlets	
number of socket-outlets	16A : 3 to 6
degree of protection against electric shock	normal protection
existence of shutters	with shutters
method of application - mounting	portable type
method of installation	-



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 25/06/2021

LABORATOIRE CENTRAL DES
INDUSTRIES ELECTRIQUES
S.A.S au capital de 15.745.984 €
RCS Nanterre B 408 369 24
1 - 92206 FONTENAY AUX ROSES

Signature **Jérôme REYSSON**
Certification Officer