

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Adaptor
Name and address of the applicant	LEGRAND FRANCE 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE
Name and address of the manufacturer	LEGRAND FRANCE 128 AVENUE DU MARECHAL DE LATTRE DE TASSIGNY 87045 LIMOGES CEDEX - FRANCE
Name and address of the factory	NINGBO BANMEN ELECTRIC APPLIANCE CO., LTD East Industrial Zone, Guanhaiwei Cixi City 315314 ZHEJIANG PROVINCE - CHINA
Note: When more than one factory, please report on page 2	<input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	16A 250V~ Max 3680W 230V~ See Annex
Trademark / Brand (if any)	legrand
Customer's Testing Facility (CTF) Stage used	/
Model / Type Ref.	0 494 31, 0 494 32
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 60884-1:2002(ed.3) +A1:2006 +A2:2013 IEC 60884-2-5:2017
As shown in the Test Report Ref. No. which forms part of this Certificate	ABND-ESH-P19122601

This CB Test Certificate is issued by the National Certification Body



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr

Date: 28/06/2020



LABORATOIRE CENTRAL DES
INDUSTRIES ELECTRIQUES
S.A.S au capital de 15.745.984 €
RCS Nanterre B 408 363 174
33 avenue du Général Leclerc
F - 92266 FONTENAY AUX ROSES

Signature: 
Julien GAUTHIER
Certification Officer

ANNEX

RATING AND MAIN CHARACTERISTICS

Product Reference	Product Range	Description	Color of enclosure
0 494 31	UC01	MOP STD FB 2P+E 16A 2 FRONT OUTLETS	WHITE/GREY
0 494 32	UC02		BLACK

CLASSIFICATION

standard Sheet: (CEE7)	V (socket-outlet) / VII (plug) of CEE 7
rated current	16 A
rated load	3680 W
rated voltage (V)	250 V
household voltage (V)	230 V
degree of protection	IP20
provision for earthing	with earthing contact
socket-outlets	
multiple socket-outlets	16A: 2
number of socket-outlets	
degree of protection against electric shock	normal protection
existence of shutters	with shutter
method of application - mounting	portable type
plugs:	
class of equipment	I



LCIE – Laboratoire Central des Industries Electriques
33, avenue du Général Leclerc – BP8
FR 92 266 Fontenay aux Roses Cedex
www.lcie.fr



Signature: *Julien GAUTHIER*
Julien GAUTHIER
Certification Officer

Date: 28/06/2020