

HTE Series

with polyamide insulating body

- UL94V-0
- mounting onto PR/3 type rails according to IEC 60715 Std., "TH/35" type
- for earth connection with yellow/green insulating body



yellow/green version	HTE.1 Cat. No. HT400	HTE.1/1+2 Cat. No. HT410	HTE.1/2+2 Cat. No. HT420
TECHNICAL CHARACTERISTICS			
function / type	earth	earth, 1 input and 2 outputs	earth, 2 inputs and 2 outputs
rated cross-section (mm ²)	1,5	1,5	1,5
connecting capacity			
flexible (mm ²)	0,2 ÷ 2,5	0,2 ÷ 2,5	0,2 ÷ 2,5
rigid (mm ²)	0,2 ÷ 2,5	0,2 ÷ 2,5	0,2 ÷ 2,5
max. flexible with ferrule (mm ²)-ferrule type	1,5 - WP15/14	1,5 - WP15/14	1,5 - WP15/14
rated voltage / rated current / gauge conf. to IEC 60947-7-1	- / - / B2	- / - / B2	- / - / B2
rated voltage / rated current / AWG	- / - / 26-14 AWG	- / - / 26-14 AWG	- / - / 26-14 AWG
rated impulse withstand voltage / pollution degree	8 KV / 3	8 KV / 3	8 KV / 3
insulation stripping length (mm)	10	10	10
height / width / thickness	43 / 50 / 4,2	43 / 61 / 4,2	43 / 65 / 4,2
height / width / thickness	51 / 50 / 4,2	51 / 61 / 4,2	51 / 65 / 4,2
height / width / thickness	-	-	-
APPROVALS			
ACCESSORIES	Type	Type	Type
End sections	grey blue		
Permanent cross connection			
Rated current carrying capacity of jumper (A)			
Cross-connection identification strip (100 mm)	green		
Multiple common bar	250 mm		
Shunting screw and sleeve			
Coloured partition	red, green, white		
Cross connection barrier	red		
Test plug socket			
Test plug			
Modular test plug			
End section for modular test plug			
Numbering strip			
Screwdriver for the activation of the spring			
Warning plate	on adjacent terminal blocks		
Marking tag	printed or blank		
End bracket			
Mounting rail according to IEC 60715 Std.			
	Cat. No.	Cat. No.	Cat. No.
	HMT.1/PT/GR	HMT.1/1+2/PT/GR	HMT.1/2+2/PT/GR
	-	-	-
	PTC/1/02 poles	PTC/1/02 poles	PTC/1/02 poles
	PTC/1/03 poles	PTC/1/03 poles	PTC/1/03 poles
	PTC/1/05 poles	PTC/1/05 poles	PTC/1/05 poles
	PTC/1/10 poles	PTC/1/10 poles	PTC/1/10 poles
	PTC/1/00 (50 poles)	PTC/1/00 (50 poles)	PTC/1/00 (50 poles)
	17,5	17,5	17,5
	PTC/SP	PTC/SP	PTC/SP
	-	-	-
	DFH/1	DFH/2	DFH/3
	DH01..	DH02..	DH03..
	DFM/500	DFM/500	DFM/500
	-	-	-
	-	-	-
	-	-	-
	-	-	-
	SHZ/1	SHZ/1	SHZ/1
	SH004	SH004	SH004
	CCH/2,5-4	CCH/2,5-4	CCH/2,5-4
	CCH02	CCH02	CCH02
	-	-	-
	SHZ/1	SHZ/1	SHZ/1
	SH004	SH004	SH004
	BTU for PR/DIN and PR/3	BTU for PR/DIN and PR/3	BTU for PR/DIN and PR/3
	BT005	BT005	BT005
	BTO	BTO	BTO
	BT007	BT007	BT007
	BT/3 for PR/3 only	BT/3 for PR/3 only	BT/3 for PR/3 only
	BT003	BT003	BT003
	-	-	-
	PR/3/AC of steel	PR/3/AC of steel	PR/3/AC of steel
	PR003	PR003	PR003
	PR/3/AS same with slots	PR/3/AS same with slots	PR/3/AS same with slots
	PR005	PR005	PR005