


HTE Series

with polyamide insulating body

- UL94V-0
- mounting onto PR/3 type rails according to IEC 60715 Std., "TH/35" type
- for earth connection with yellow/green insulating body



yellow/green version	HTE.6	HTE.10	HTE.16
	Cat. No. HT320	Cat. No. HT330	Cat. No. HT340
TECHNICAL CHARACTERISTICS			
function / type	earth	earth	earth
rated cross-section (mm ²)	6	10	16
connecting capacity			
flexible (mm ²)	0,2 ÷ 10	1,5 ÷ 16	1,5 ÷ 25
rigid (mm ²)	0,2 ÷ 10	1,5 ÷ 16	1,5 ÷ 25
max. flexible with ferrule (mm ²)-ferrule type	6 - WP60/20	10 - WP100/21	16 - WP160/22
rated voltage / rated current / gauge conf. to IEC 60947-7-1	- / - / A5	- / - / A6	- / - / A7
rated voltage / rated current / AWG UL	- / - / 24-8 AWG	-	-
rated impulse withstand voltage / pollution degree	8 KV / 3	12 KV / 3	12 KV / 3
insulation stripping length (mm)	18	18	18
height / width / thickness	44 / 62 / 8,2	53 / 71 / 10	56 / 80 / 12
height / width / thickness	52 / 62 / 8,2	61 / 70 / 10	64 / 80 / 12
height / width / thickness	-	-	-
		KEMA-KEUR, UL, cUL, ENEL Distribuzione pending	KEMA-KEUR, UL, cUL, ENEL Distribuzione pending
APPROVALS			
ACCESSORIES	Type	Type	Type
End sections	HMT.6/PT/GR	HMT.10/PT	HMT.16/PT
grey blue	HM321GR	HM331GR	HM341GR
Permanent cross connection	PTC/8/02 poles	PTC/11/02 poles	PTC/16/02 poles
	PTC/8/03 poles	PTC/11/03 poles	PTC/16/03 poles
	PTC/8/05 poles	PTC/11/05 poles	PTC/16/05 poles
	PTC/8/10 poles	PTC/11/10 poles	PTC/16/10 poles
	PTC/8/00 (30 poles)	PTC/11/00 (25 poles)	PTC/16/00 (20 poles)
Rated current carrying capacity of jumper (A)	41	57	76
Cross-connection identification strip (100 mm)	PTC/SP	-	-
green	PTC0990	-	-
Multiple common bar	-	-	-
250 mm	-	-	-
Shunting screw and sleeve	-	-	-
Coloured partition	DFH/1	DFH/4	DFH/4
red, green, white	DH01..	DH04..	DH04..
Cross connection barrier	-	-	-
red	-	-	-
Test plug socket	SDD/1	SDD/1	SDD/1
Test plug	DD001	DD001	DD001
Modular test plug	-	-	-
End section for modular test plug	-	-	-
Numbering strip	CNU/8/51	SNZ/10	-
Screwdriver for the activation of the spring	NU0851	SN005	-
Warning plate	CCH/2,5-4	CCH/4	CCH/4
on adjacent terminal blocks	CCH02	CCH02	CCH02
Marking tag	CNU/8/51	CNU/8/51	CNU/8/51
printed or blank	NU0851	NU0851	NU0851
End bracket	BTU for PR/DIN and PR/3	BTU for PR/DIN and PR/3	BTU for PR/DIN and PR/3
	BT005	BT005	BT005
	BTO	BTO	BTO
	BT007	BT007	BT007
	BT/3 for PR/3 only	BT/3 for PR/3 only	BT/3 for PR/3 only
	BT003	BT003	BT003
Mounting rail according to IEC 60715 Std.	-	-	-
	PR/3/AC of steel	PR/3/AC of steel	PR/3/AC of steel
	PR003	PR003	PR003
	PR/3/AS same with slots	PR/3/AS same with slots	PR/3/AS same with slots
	PR005	PR005	PR005