


## Synthetic protective conduits ROHRflex® PA 12



EN 45545-2

HL 2



### Synthetic protective conduits ROHRflex® PA 12

- ROHRflex® PA 12
- Black

|                        |   |
|------------------------|---|
| <b>Order number:</b>   | <b>0236.202.016</b>   |
| E-No:                  | 125191400   |
| EAN:                   | 7611614090849   |
| Material               | Polyamide PA 12   |
| Fire classification    | V2 (UL 94)  |
| Properties             | High reciprocal flexural resistance, improved insulation properties, air- and liquid-tight, oil and petrol resistant, basically resistant to acids and solvents, free of silicone, free of cadmium, halogen-free, self extinguishing. Black tubing is UV-resist |
| Application            | Machine and plant constructions, vehicle construction, rail vehicles outside applications, shipbuilding, automation, electrical installations   |
| Protection class       | IP 68 / IP 69   |
| Operation temperature  | -50°C / +100°C / ^ +130°C   |
| Outer diameter         | 21.2 mm   |
| Inner diameter         | 16.5 mm   |
| Bending radius static  | 35 mm   |
| Bending radius dynamic | 75 mm   |
| Dispatch               | 50  |

#### Available on request:

- Synthetic protective conduits ROHRflex® PA 12 in orange for electric vehicles