

## Long entry thread metric



### AGRO combination conduit glands Progress® nickel-plated brass with integrated cable gland

#### Type approval: Progress MS Kombi

- Connector for tubing with AD mm
- Two-piece sealing insert
- overall length insulated

|                                    |   |
|------------------------------------|---|
| <b>Order number:</b>               | <b>1710.60.12.10</b>  |
| E-No:                              | 126658300   |
| EAN:                               | 7611614144177   |
| Material                           | Nickel-plated brass   |
| Seal                               | TPE   |
| O-ring                             | NBR   |
| Operation temperature              | -40°C / +100°C  |
| Strain relief                      | Version A acc. to EN 62444                                    |
| Protection class                   | Cable gland IP 68   |
| Note                               | The max. clamping range depends on the conduit inner diameter |
| Entry thread                       | M12x1.5   |
| Outer diameter                     | 10 mm   |
| Clamping range with insert min.    | - mm  |
| Clamping range with insert max.    | - mm  |
| Clamping range without insert min. | 5.0 mm  |
| Clamping range without insert max. | 6.5 mm  |
| Wrench size                        | 15/17 mm  |
| Dimension H                        | 33 mm   |
| Thread length L                    | 10 mm   |
| Dispatch                           | 50  |

Depending on the type of conduit, the stabilising bush must be ordered separately. Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.