




CE

Power	6 W	Voltage	230 V
Luminous flux*	750 lm (360°)	Colour temperature	3000 K
Light colour	WW	Beam angle	110 °
IK	06	Protection class	IP20




See more on dedicated page 



 Declaration of Conformity



 Photometric file



 3D model

Technical data:

Product code	SLI037027WW_PW
Power	6 W
Nominal current	48 mA
Voltage	230 V
Energy consumption	6 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.5
Useful luminous flux*	750 lm (360°)
Luminous flux**	550 lm (360°)
Light efficiency	122 lm/W
Luminous intensity	220 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	110 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	115x35 mm
Mounting hole	95 mm
Weight	0.15 kg
For use	Inside
Assembly method	NATYNK/PODTYNK
Application	Inside
Made in	PRC



*Applies to the LED source used. **Luminaire luminous flux