



| | | | |
|------------------|-----------------------------|--------------------|---------------|
| Power | 20 (5,6) W | Voltage | 12 V |
| Luminous flux** | 1950 (480) lm (360°) | Colour temperature | 6000 K |
| Light colour | CW | Beam angle | 120 ° |
| Protection class | IP44 | | |



 Declaration of Conformity

Technical data:

| | |
|------------------------------|----------------------|
| Product code | WOJ+11989_20 |
| Power | 20 (5,6) W |
| Nominal current | 1670 mA |
| Voltage | 12 V |
| Energy efficiency classe | G |
| Energy consumption | 3 kWh/1000h |
| Frequency | DC Hz |
| Power supply included | No |
| Power factor | 1 |
| Luminous flux** | 1950 (480) lm (360°) |
| Light efficiency | 98 lm/W |
| Colour temperature | 6000 K |
| Light colour | CW |
| Beam angle | 120 ° |
| RA | 90 |
| Uniformity of color SDCM max | 5 |
| Dimmable | Yes |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Protection class | IP44 |
| Dimension (axbxc) | 8X5000 mm |
| Weight | 0.032 kg |
| For use | Inside |
| Application | INT |
| Made in | PRC |
| Other | 1m-460mA , |

