




CE

|                  |                       |                    |               |
|------------------|-----------------------|--------------------|---------------|
| Power            | <b>50 W</b>           | Voltage            | <b>230 V</b>  |
| Luminous flux*   | <b>4000 lm (120°)</b> | Colour temperature | <b>6000 K</b> |
| Light colour     | <b>CW</b>             | Beam angle         | <b>100 °</b>  |
| Protection class | <b>IP65</b>           |                    |               |



See more on dedicated page 



 Declaration of Conformity



 Photometric file

**Technical data:**

|                              |                     |
|------------------------------|---------------------|
| Product code                 | SLI029044CW         |
| Power                        | 50 W                |
| Nominal current              | 230 mA              |
| Voltage                      | 230 V               |
| Energy consumption           | 50 kWh/1000h        |
| Frequency                    | 50HZ Hz             |
| Protection class             | I                   |
| Power supply included        | +                   |
| Power factor                 | 0.9                 |
| Useful luminous flux*        | 4000 lm (120°)      |
| Luminous flux**              | 3900/4000 lm (360°) |
| Light efficiency             | 78 lm/W             |
| Colour temperature           | 6000 K              |
| Light colour                 | CW                  |
| Beam angle                   | 100 °               |
| RA                           | 80                  |
| Uniformity of color SDCM max | 5                   |
| Dimmable                     | No                  |
| Working temperature range    | -20/+40 °           |
| Lifespan                     | 17000 h             |
| Housing material             | Aluminum, GLASS     |
| Protection class             | IP65                |
| Colour                       | White               |
| Dimension (axbxc)            | 160x205x31 mm       |
| Weight                       | 0.7 kg              |
| For use                      | Inside/Outside      |
| Assembly method              | On the ceiling      |
| Application                  | INT/EXT             |
| Made in                      | PRC                 |



\*Applies to the LED source used. \*\*Luminaire luminous flux