




Power	<b>30 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>2900 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Light colour	<b>CW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Protection class	<b>IP44</b>




See more on dedicated page 




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029050CW_CZUJNIK_PW
Power	30 W
Nominal current	130 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2900 lm (120°)
Luminous flux**	2900 lm (360°)
Light efficiency	97 lm/W
Colour temperature	6000 K
Light colour	CW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Protection class	IP44
Colour	Black
Dimension (axbxc)	150x190x53 mm
Weight	0.393 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux