







CE

Power	<b>50 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>4500 lm (120°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Protection class	<b>IP44</b>

See more on dedicated page  Declaration of Conformity Photometric file

**Technical data:**

Product code	SLI029055NW_CZUJNIK_PW
Power	50 W
Nominal current	220 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4500 lm (120°)
Luminous flux**	4500 lm (360°)
Light efficiency	90 lm/W
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Protection class	IP44
Colour	White
Dimension (axbxc)	180x215x53 mm
Weight	0.579 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux