



| | | | |
|------------------|-----------------------|--------------------|--------------------|
| Power | 36 W | Voltage | 230 V |
| Luminous flux* | 2840 lm (120°) | Colour temperature | 2700-6500 K |
| Light colour | CCT | Beam angle | 120 ° |
| Protection class | IP20 | | |



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|----------------|
| Product code | SLI031032CCT |
| Power | 36 W |
| Nominal current | 165 mA |
| Voltage | 230 V |
| Energy efficiency classe | F |
| Energy consumption | 36 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.9 |
| Useful luminous flux* | 2840 lm (120°) |
| Luminous flux** | 2840 lm (360°) |
| Light efficiency | 79 lm/W |
| Colour temperature | 2700-6500 K |
| Light colour | CCT |
| Beam angle | 120 ° |
| RA | 80 |
| Light source included | + |
| Uniformity of color SDCM max | 5 |
| Dimmable | SMART |
| Working temperature range | -20/+40 ° |
| Lifespan | 17000 h |
| Housing material | PC |
| Protection class | IP20 |
| Colour | White |
| Dimension (axbxc) | 488x72 mm |
| Weight | 1.87 kg |
| For use | Inside |
| Assembly method | On the ceiling |
| Application | INT |
| Made in | PRC |



*Applies to the LED source used, **Luminaire luminous flux

*Luminaire with the ability to change the color of light (2700 - 6500K) or dimming by application Spectrum SMART.