




Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>8700 lm (120°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>100 °</b>
IK	<b>07</b>	Protection class	<b>IP65</b>



See more on dedicated page 




 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI029047WW_PW
Power	100 W
Nominal current	435 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.5
Useful luminous flux*	8700 lm (120°)
Luminous flux**	8700 lm (360°)
Light efficiency	86 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	100 °
RA	>70
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
IK	07
Protection class	IP65
Colour	White
Dimension (axbxc)	270x210x27 mm
Weight	1.256 kg
For use	Outside
Assembly method	On the ceiling
Application	EXT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux