



Power	40 W	Voltage	230 V
Luminous flux*	4600 lm (120°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	100 °
IK	10	Protection class	IP44



See more on dedicated page 



 User manual



 Declaration of Conformity



 Photometric file

Technical data:

Product code	SLI028036NW
Power	40 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.96
Useful luminous flux*	4600 lm (120°)
Luminous flux**	4600 lm (360°)
Light efficiency	115 lm/W
Luminous intensity	1700 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	100 °
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	TWORZYWO SZTUCZNE - PC
IK	10
Protection class	IP44
Colour	White
Dimension (axbxc)	1200x110x60 mm
Weight	1.56 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Made in	PRC
Other	dane na moduł Fi use=4600 P=40W ,



*Applies to the LED source used. **Luminaire luminous flux