



CE

Power **15-27 W**

Colour temperature **4000 K**

Beam angle **36, 60 °**

Voltage **230 V**


Light colour **Neutral white**

Protection class **IP20**



 Declaration of Conformity



 Photometric file

**Technical data:**

Product code	SLI033021NW_PW
Power	15-27 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	3200 lm (360°)
Luminous flux**	1600-2600 lm (360°)
Light efficiency	119 lm/W
Luminous intensity	6100 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	Black
Dimension (axbxc)	74x170x170 mm
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



\*Applies to the LED source used. \*\*Luminaire luminous flux