



---


Power	<b>35 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3850 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Light colour	<b>WW</b>	Beam angle	<b>120 °</b>
IK	<b>06</b>	Protection class	<b>IP20</b>

---

SLI035070WW\_35W\_DIM

**Technical data:**

Product code	SLI035070WW_35W_DIM
Power	35 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency classe	E
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3850 lm (360°)
Luminous flux**	3850 lm (360°)
Light efficiency	110 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	DIM
Working temperature range	-20/+40 °
Lifespan	25000 h
Housing material	Aluminum, PLASTIC
IK	06
Protection class	IP20
Colour	White
Dimension (axbxc)	620x620x10 mm
Mounting hole	600x600 mm
For use	Inside
Assembly method	Recessed/On the ceiling/Suspended
Application	INT
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux