




| | | | |
|------------------|---------------------|--------------------|---------------|
| Power | 5 W | Voltage | 24 V |
| Luminous flux* | 230 lm (90°) | Colour temperature | 3000 K |
| Light colour | WW | Beam angle | 25 ° |
| Protection class | IP65 | | |




 Declaration of Conformity



 Photometric file

Technical data:

| | |
|------------------------------|----------------|
| Product code | SLI002017WW |
| Power | 5 W |
| Nominal current | 210 mA |
| Voltage | 24 V |
| Energy efficiency classe | G |
| Energy consumption | 6 kWh/1000h |
| Frequency | DC Hz |
| Protection class | III |
| Power supply included | + |
| Power factor | 1 |
| Useful luminous flux* | 230 lm (90°) |
| Luminous flux** | 230 lm (360°) |
| Light efficiency | 46 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 25 ° |
| RA | 70 |
| Light source included | + |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 6 |
| Dimmable | Yes |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP65 |
| Colour | Gray |
| Dimension (axbxc) | 64x100 mm |
| Weight | 0.47 kg |
| For use | Inside/Outside |
| Assembly method | On the ceiling |
| Application | INT/EXT |
| Made in | PRC |



*Applies to the LED source used. **Luminaire luminous flux
Requires 24V power supply.