




CE

| | | | |
|----------------|------------------------|--------------------|---------------|
| Power | 75 W | Voltage | 230 V |
| Luminous flux* | 13000 lm (360°) | Colour temperature | 4000 K |
| Light colour | Neutral white | Beam angle | 120 ° |
| IK | 10 | Protection class | IP65 |

See more on dedicated page  Photometric file

Technical data:

| | |
|------------------------------|--------------------------|
| Product code | SLI028027NW_PW_BLACK |
| Power | 75 W |
| Nominal current | 332 mA |
| Voltage | 230 V |
| Energy consumption | 75 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Power factor | 0.99 |
| Useful luminous flux* | 13000 lm (360°) |
| Luminous flux** | 11200 lm (360°) |
| Light efficiency | 173 lm/W |
| Luminous intensity | 3600 cd |
| Colour temperature | 4000 K |
| Light colour | Neutral white |
| Beam angle | 120 ° |
| RA | 80 |
| Uniformity of color SDCM max | 3 |
| Dimmable | No |
| Working temperature range | -25/+40 ° |
| Lifespan | 50000 h |
| Housing material | POLYCARBONATE |
| IK | 10 |
| Protection class | IP65 |
| Colour | Black/White |
| Dimension (axbxc) | 1490x72x70 mm |
| Weight | 1.3917 kg |
| For use | Inside/Outside |
| Assembly method | On the ceiling/Suspended |
| Application | INT/EXT |
| Made in | PRC |
| Other | MAX 10 pcs per line , |



*Applies to the LED source used. **Luminaire luminous flux