



Power **19 W**
Colour temperature **3000 K**
Beam angle **24 °**

Voltage **230 V**
Light colour **WW**
Protection class **IP20**

MDR48PRO1983024S_CASAMBI

Technical data:

| | |
|------------------------------|---------------------|
| Product code | WOJP07687 |
| Power | 19 W |
| Nominal current | 90.9 mA |
| Voltage | 230 V |
| Energy consumption | 19 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | I |
| Power supply included | + |
| Manufacturer of power supply | TCI |
| Power factor | 0.93 |
| Useful luminous flux* | 2660 lm (360°) |
| Luminous flux** | 1710 lm (360°) |
| Light efficiency | 140 lm/W |
| Colour temperature | 3000 K |
| Light colour | WW |
| Beam angle | 24 ° |
| RA | 80 |
| Light source included | + |
| Producer of LED diodes | CREE |
| Uniformity of color SDCM max | 3 |
| Dimmable | CASAMBI |
| Working temperature range | -20/+40 ° |
| Lifespan | 50000 h |
| Housing material | Aluminum |
| Protection class | IP20 |
| Colour | Black |
| Dimension (axbxc) | 90x200x165 mm |
| Weight | 0.86 kg |
| For use | Inside |
| Assembly method | On 3-circuit system |
| Application | Inside |
| Made in | PL |
| Other | L90B10 - 73000h , |



*Applies to the LED source used. **Luminaire luminous flux