



---

Power	<b>27 W</b>
Colour temperature	<b>3000 K</b>
Beam angle	<b>60 °</b>

Voltage	<b>230 V</b>
Light colour	<b>WW</b>
Protection class	<b>IP20</b>

---

MDR48PRO2783060G\_CASAMBI

**Technical data:**

Product code	WOJP07670
Power	27 W
Nominal current	129.1 mA
Voltage	230 V
Energy consumption	27 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Manufacturer of power supply	TCI
Power factor	0.93
Useful luminous flux*	3510 lm (360°)
Luminous flux**	2430 lm (360°)
Light efficiency	130 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	60 °
RA	80
Light source included	+
Producer of LED diodes	CREE
Uniformity of color SDCM max	3
Dimmable	CASAMBI
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	ZŁOTY
Dimension (axbxc)	90x200x165 mm
Weight	0.86 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PL
Other	L90B10 - 73000h ,



\*Applies to the LED source used. \*\*Luminaire luminous flux