




Power	<b>30 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>3000 K</b>	Light colour	<b>WW</b>
Beam angle	<b>50 °</b>	Protection class	<b>IP20</b>



See more on dedicated page 



 3D model

ALD9PR03093050BB\_DALI

**Technical data:**

Product code	WOJP07024
Power	30 W
Nominal current	143 mA
Voltage	230 V
Energy consumption	35 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Manufacturer of power supply	TRIDONIC
Power factor	0.93
Useful luminous flux*	3750 lm (360°)
Luminous flux**	3750 lm (360°)
Light efficiency	125 lm/W
Colour temperature	3000 K
Light colour	WW
Beam angle	50 °
RA	90
Light source included	+
Producer of LED diodes	SAMSUNG
Uniformity of color SDCM max	3
Dimmable	OPC
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum
Protection class	IP20
Colour	Black
Dimension (axbxc)	1120X444X74 mm
Weight	2.2 kg
For use	Inside
Assembly method	On the ceiling/Suspended
Application	Inside
Made in	PL
Other	L90B10 - 74000h ,



\*Applies to the LED source used. \*\*Luminaire luminous flux