

WLD

WLD+40002\_SMART



CE

Power **6 W**

Voltage **48 V**

Colour temperature **3000/4000/6000 K**

Light colour **CCT**

Beam angle **24 °**

Protection class **IP20**



 Declaration of Conformity

Technical data:

|                              |                  |
|------------------------------|------------------|
| Product code                 | WLD+40002_SMART  |
| Power                        | 6 W              |
| Nominal current              | 115 mA           |
| Voltage                      | 48 V             |
| Energy consumption           | 6 kWh/1000h      |
| Frequency                    | DC Hz            |
| Protection class             | III              |
| Power factor                 | 1                |
| Useful luminous flux*        | 500 lm (360°)    |
| Luminous flux**              | 350 lm (360°)    |
| Light efficiency             | 83 lm/W          |
| Luminous intensity           | 1050 cd          |
| Colour temperature           | 3000/4000/6000 K |
| Light colour                 | CCT              |
| Beam angle                   | 24 °             |
| RA                           | >90              |
| Light source included        | Yes              |
| Uniformity of color SDCM max | 5                |
| Working temperature range    | -20 to +40 °     |
| Lifespan                     | 50000 h          |
| Housing material             | AL+PC            |
| Protection class             | IP20             |
| Colour                       | White            |
| Dimension (axbxc)            | 35x140x178 mm    |
| For use                      | Inside           |
| Assembly method              | NA SZYŃĘ         |
| Application                  | Inside           |
| Made in                      | PRC              |
| Other                        | CCT/DIM ,        |



\*Applies to the LED source used. \*\*Luminaire luminous flux