


**CE**Power **6 W**Colour temperature **3000 K**Beam angle **24 °**Voltage **48 V**Light colour **WW**Protection class **IP20**

**Technical data:**

|                              |                   |
|------------------------------|-------------------|
| Product code                 | WLD+40004_CASAMBI |
| Power                        | 6 W               |
| Nominal current              | 115 mA            |
| Voltage                      | 48 V              |
| Energy consumption           | 6 kWh/1000h       |
| Frequency                    | DC Hz             |
| Protection class             | III               |
| Manufacturer of power supply | tuobo             |
| Power factor                 | 1                 |
| Useful luminous flux*        | 555 lm (360°)     |
| Luminous flux**              | 370 lm (360°)     |
| Light efficiency             | 93 lm/W           |
| Luminous intensity           | 1050 cd           |
| Colour temperature           | 3000 K            |
| Light colour                 | WW                |
| Beam angle                   | 24 °              |
| RA                           | >90               |
| Light source included        | Yes               |
| Producer of LED diodes       | osram             |
| Uniformity of color SDCM max | 5                 |
| Dimmable                     | CASAMBI           |
| Working temperature range    | -20 to +40 °      |
| Lifespan                     | 50000 h           |
| Housing material             | AL+PC             |
| Protection class             | IP20              |
| Colour                       | Black             |
| Dimension (axbxc)            | 35x140x178 mm     |
| For use                      | Inside            |
| Assembly method              | NA SZYNE          |
| Application                  | Inside            |
| Made in                      | PRC               |
| Other                        | CASAMBI ,         |



\*Applies to the LED source used. \*\*Luminaire luminous flux