

LIGHT SB FO E P CI WRU SRC 47 (787 231)



Figure without obligation

| Type | LIGHT SB FO E P CI WRU SRC 47 |
|---|--|
| Part No. | 787 231 (part) |
| Standard | EN ISO 20345:2011 |
| Size | 47 |
| Material | Leather |
| Lining | Textile |
| Classification as per EN ISO 20345:2011 | Class I |
| Protection class as per EN ISO 20345:2011 | SB |
| Shoe shape | B |
| Protective cap | Plastic |
| Sealed with | Shoelaces |
| Sole type | Polyurethane |
| Penetration protection | Composite textile material |
| Metal-free equipment | Yes |
| Colour | Black / orange |
| Application | Electrical engineering |
| Special properties | The outsole provides electrical insulation at voltages up to 1,000 V – M Ω > 1,000 if requirements are met (no moisture, does not refer to the upper shaft). Electrical resistance acc. Canadian standard CSA Z 195 14 Increase by 1 kV/s Voltage 20,000 V / 60 Hz duration of 1 minute. Electrical resistance acc. the ASTM 2413 -11 standard increase of 1 kV/sec Voltage 20,000 V / 60 Hz duration of 1 minute. Requirement of electric flow lower than 1.0 mA. |
| Weight | 1 Pa/pc(s) |
| Customs tariff number (Comb. Nomenclature EU) | 64039193 |
| GTIN | 4013364508156 |
| PU | 1 Pa |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.