


DSH ZP B2 LSG A TT 255 (909 131)


- Type 1 + type 2 + type 3 combined arrester based on spark gap technology, meets the minimum requirements of IEC 60364-5-53 clause 534 for the nominal discharge current capacity I_n and the lightning current discharge capacity I_{imp} in case of overhead line supply
- Easy, fast and completely toolless installation by snapping the arrester on 40 mm busbar systems
- Capable of protecting terminal equipment
- Includes a 230 V power supply (N and L) for the compartment for additional applications / termination point meter mounting board according to VDE-AR-N 4100
- Includes a single-pole B6 circuit breaker for power supply
- A sealable protective cover and 2 x sockets and 2 x plugs for easy wiring of the intelligent measuring system are included in delivery



Figure without obligation



Basic circuit diagram DSH ZP B2 LSG A TT 255



Dimension drawing DSH ZP B2 LSG A TT 255

Combined arrester for TT and TN-S systems for use in the main power supply system (3+1 configuration) of buildings without external lightning protection (also with overhead line supply).

Type	DSH ZP B2 LSG A TT 255
Part No.	909 131 NEW
SPD according to EN 61643-11 / IEC 61643-11	type 1 + type 2 + type 3 / class I + class II + class III
Energy coordination with terminal equipment (≤ 10 m)	type 1 + type 2 + type 3
Nominal voltage (a.c.) (U_N)	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) (U_C)	255 V (50 / 60 Hz)
Lightning impulse current (10/350 μ s) [$L1+L2+L3+N-PE$] (I_{total})	30 kA
Lightning impulse current (10/350 μ s) [$L-N$] (I_{imp})	7.5 kA
Specific energy [$L-N$] (W/R)	14.06 kJ/ohms
Lightning impulse current (10/350 μ s) [$N-PE$] (I_{imp})	30 kA
Specific energy [$N-PE$] (W/R)	225 kJ/Ohm
Nominal discharge current (8/20 μ s) [$L-N$]/[$N-PE$] (I_n)	20 / 80 kA
Voltage protection level [$L-N$] (U_P)	≤ 1.5 kV
Voltage protection level [$N-PE$] (U_P)	≤ 1.5 kV
Open-circuit voltage of the combination wave generator (U_{oc})	20 kV
Follow current extinguishing capability [$L-N$] (a.c.) (I_{fi})	25 kA _{rms}
Follow current extinguishing capability [$N-PE$] (a.c.) (I_{fi})	100 A _{rms}
Follow current limitation / Selectivity	no tripping of a 32 A gG fuse up to 25 kA _{rms} (prosp.)
Max. mains-side overcurrent protection	160 A gG
Temporary overvoltage (TOV) [$L-N$] (U_T) – Characteristic	440 V / 120 min. – withstand
Temporary overvoltage (TOV) [$N-PE$] (U_T) – Characteristic	1200 V / 200 ms – withstand
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (PEN, $\frac{1}{2}$)	16-25 mm ² flexible / 16-35 mm ² stranded
For mounting on	40 mm busbar systems
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 30 (in combination with cover)
Approvals	VDE
Power supply (for compartment for additional applications / termination point meter mounting board according to VDE-AR-N 4100) (U_N)	230 V
Suitable circuit breakers (manufacturer, type)	ABB S201P-B6, Hager MB199
Rated current of the circuit breaker (I_n)	6 A
Tripping characteristic	B
Extended technical data:	
Protection level [$L-PE$] (U_P)	≤ 1.6 kV
Weight	769 g
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364449749



Type	DSH ZP B2 LSG A TT 255
Part No.	909 131 NEW
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.