


**DG MP TNS 385 FM (942 409)**


- Prewired complete unit consisting of a base part and remote signalling contact connection with push-in connection system and plug-in protection modules
- High discharge capacity due to heavy-duty zinc oxide varistors / spark gaps
- High reliability due to "Thermo Dynamic Control" SPD monitoring device



Figure without obligation



Basic circuit diagram DG MP TNS 385 FM



Dimension drawing DG MP TNS 385 FM

Modular surge arrester for use in TN-S systems; with floating remote signalling contact.

Type Part No.	DG MP TNS 385 FM 942 409
SPD according to EN 61643-11 / IEC 61643-11	type 2 + type 3 / class II + class III
Energy coordination with terminal equipment (≤ 10 m)	type 2 + type 3
Nominal voltage (a.c.) (U <sub>n</sub> )	230 / 400 V (50 / 60 Hz)
Max. continuous operating voltage (a.c.) (U <sub>c</sub> )	385 V (50 / 60 Hz)
Nominal discharge current (8/20 μs) (I <sub>n</sub> )	20 kA
Max. discharge current (8/20 μs) (I <sub>max</sub> )	40 kA
Combination wave [L-N] (U <sub>oc</sub> )	20 kV
Nominal load current for "V-connection" (I <sub>L</sub> )	40 A
Voltage protection level [L-PE]/[N-PE] (U <sub>p</sub> )	≤ 1.75 / ≤ 1.75 kV
Voltage protection level [L-PE]/[N-PE] at 5 kA (U <sub>p</sub> )	≤ 1.35 / ≤ 1.35 kV
Response time (t <sub>a</sub> )	≤ 25 ns
Max. mains-side overcurrent protection with "V-connection"	40 A gG
Max. mains-side overcurrent protection with stub wiring (double connection 2 x 10 mm <sup>2</sup> )	125 A gG
Short-circuit withstand capability for max. mains-side overcurrent protection (I <sub>SCCR</sub> )	25 kA <sub>rms</sub>
Temporary overvoltage (TOV) (U <sub>T</sub> ) – Characteristic	335 V / 5 sec. – withstand
Temporary overvoltage (TOV) (U <sub>T</sub> ) – Characteristic	440 V / 120 min. – withstand
Operating temperature range (T <sub>U</sub> )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm <sup>2</sup> solid
Cross-sectional area (min.)	6 mm <sup>2</sup> flexible
Cross-sectional area (max.)	10 mm <sup>2</sup> solid / flexible
Cross-sectional area (min.) with wire end ferrule	1.5 mm <sup>2</sup>
Cross-sectional area (max.) with wire end ferrule	6 mm <sup>2</sup>
Cross-sectional area (max.) with wire end ferrule without collar	10 mm <sup>2</sup>
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	4 module(s), DIN 43880
Approvals	KEMA, VDE
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid / flexible
<b>Weight</b>	<b>378 g</b>
<b>Customs tariff number (Comb. Nomenclature EU)</b>	<b>85363030</b>
<b>GTIN</b>	<b>4013364484832</b>
<b>PU</b>	<b>1 pc(s)</b>

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.