


## PCE data sheet

article#	<b>2351-9</b>
article description	<b>CEE-connector 63A 5p 9h IP44 POWER TWIST</b>
description long	CEE-connector 63A 5p 9h IP44 POWER TWIST housing material: PA6 rated current: 63A number of poles: 5 (3P+N+PE) clock-position: 9h rated voltage/frequency: 120/208V~ - 144/250V~ / 50+60Hz contacts: brass, with lamellar spring (CuBe) connection technology: frame terminals with screws IP protection class: IP44
GTIN (EAN)	9003399872648
country of origin	AT
customs number	85366990
net weight	0.720 kg
packaging quantity	2
minimum order quantity	2

ETIM 8.0	EC001320
IEC-amperage	63 A
Number of poles	5
Voltage acc. EN 60309-2	200-250 V (50+60 Hz) blue
Clock hour position	9 h
Identification colour	Blue
RAL-number	7046
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Angle of plug	Straight
Cable entry	Swivel
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated

a	269 mm
b	107 mm
K (cable Ø)	14,5-36 mm
SW	61 mm
wire flexible	6-16 mm <sup>2</sup>
contact screws	200 Ncm
strain relief	1500 Ncm
dismantling length	100 mm
stripping length	15-18 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=2351-9>



[www.manufacturer-safety.info](http://www.manufacturer-safety.info)