



PCE data sheet

article#	125-6x
article description	CEE-wall mounted socket 32A 5p 6h IP44 black
description long	CEE-Wandsteckdose 32A 5p 6h IP44 schwarz Schraubklemme Gehäusematerial: PA6 Bauform: halbrundes Gehäuse Leitungseinführung von oben oder hinten inkl. Würfenippelkontakte: Messing blank Schutzart: IP44
GTIN (EAN)	9003399930119
country of origin	AT
customs number	85366990
net weight	0.319 kg
packaging quantity	10

ETIM 7.0	EC001321
Model	Surface mounted (plaster)
IEC-amperage	32 A
Number of poles	5
Voltage acc. EN 60309-2	400 V (50+60 Hz) red
Clock hour position	6 h
Identification colour	Red
RAL-number	9005
Degree of protection (IP)	IP44
Connection system	Screwed terminal
Cable entry	Swivel
Material	Plastic
Contact material	CuZn
Surface finish contacts	Untreated
Type of fastening	Inner lying mounting

wire flexible	2,5-6 mm ²
wire solid	2,5-10 mm ²
contact screws	110 Ncm
dismantling length	50 mm
stripping length	12-14 mm



b=Höhe/height
Neigung/angle=15°



www.manufacturer-safety.info