





CE

Power	<b>9 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>1000 lm (360°)</b>	Colour temperature	<b>3000/4000/6000 K</b>
Light colour	<b>CCT</b>	Beam angle	<b>30 °</b>
Protection class	<b>IP54</b>		




 User manual



 Declaration of Conformity

Technical data:

Product code	SLI003025CCT_PW
Power	9 W
Nominal current	65 mA
Voltage	230 V
Energy consumption	9 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.5
Useful luminous flux*	1000 lm (360°)
Luminous flux**	700 lm (360°)
Light efficiency	111 lm/W
Colour temperature	3000/4000/6000 K
Light colour	CCT
Beam angle	30 °
RA	80
Light source included	+
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Protection class	IP54
Colour	Black
Dimension (axbxc)	99x78x156 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC
Other	Funkcja zmiany barwy światła 3000K/4000K/6000K ,



\*Applies to the LED source used. \*\*Luminaire luminous flux