

BRUSHLESS HAMMER DRILL WITH CHISELING FUNCTION 18V



Product description

HT2E228-0CH : A versatile and efficient device for drilling in concrete, ceramics, stone, wood, metal and for chiselling in plaster and wall cladding. Function for smooth chisel blade position adjustment, enabling its adaptation to surfaces at different angles. The pneumatic impact drive mechanism with a force of 2.0 J at an impact frequency of 0–4600 IPM and a rotational speed of 0–1300 RPM allows for faster and effective drilling in walls and hacking. SDS+ handle enables rapid and comfortable drill bit and chisel exchange, without the need to use additional tools. Brushless motor with innovative construction, thanks to the elimination of brush friction and special magnets offers greater power, longer operation time and lifespan of the device. Advanced electronic circuits continuously regulate the motor operation, optimizing its power according to the performed activity, which translates into efficiency and maximization of the battery operation time. Gearbox made of metal enhances the wear resistance and ensures precision of the mechanism. Comfortably located switch enables selecting one of the functions: non-impact drilling, impact drilling, impact chiselling with rotation switch, rotation. Smooth adjustment of the rotational speed in the power switch provides full control over the conducted operation. Soft handle enables more reassuring hold of the power tool and dampens vibrations during operation. The additional handle enables better control of the tool during more demanding works. The built-in, powerful LED illuminates the work areas perfectly. Changing the rotation of the power tool in both directions enable drilling, and unscrewing. OneAccuSystem 18 V enables using the selected battery in a wide and diverse range of power tools for the most heavy-duty work. HT2E242-C60: An efficient charger that will charge a 2 Ah battery in just approx. 30 min. An advanced electronic module monitors battery voltage and temperature to maximise the efficiency of the charging process and ensure long battery life. Overheating protection extends the use life and battery life. Current short circuit protection improves the safety of the charging process. Monitoring the charge level of the cells extends their life. Indicators show the battery status and inform about the charging process. HT2E240-A40: Perfectly balanced in terms of low weight, small size, and capacity, a rechargeable battery for many different tools offered by the brand. An advanced electronic module monitors battery operation to maximize performance, operating time, increase durability and safety. Cell overheating protection, extending their operating time and enhancing their durability. Short circuit protection increases safety of work and storage of the rechargeable battery. Charging level control extends the life cycle of the cells. Cells made in the latest lithium-ion (Li-Ion) technology ensure high energy efficiency, robustness and reliability. Housing protected with rubber bumpers protects against mechanical damage. Cell protection against moisture. Operation possible from - 18 °C of external temperature, extends the scale of tool use. Charging level shows the available energy.

Characteristics

HT2E228-0CH:

- Selection of functions: non-impact drilling, impact drilling, impact chiselling with rotation switch, rotation.
- Smooth chisel position adjustment.

- Impact energy 2.0 J.
- Rotational speed: 0–1300 RPM.
- Impact Rate: 0–4600 IPM.
- Maximum wood drilling diameter – 28 mm.
- Maximum steel drilling diameter – 13 mm.
- Maximum concrete drilling diameter – 16 mm.
- Metal gearbox mechanism.
- LED light.
- Smooth speed adjustment in the power switch.
- Anti-vibration, soft handle.
- Additional, stabilising handle for the heavy duty works.
- Right and left rotation direction switch.
- Weight – 1.69 kg.
- EAN code – 5902801441370.
- 3 years warranty (after the tool is registered).
- Brushless motor.
- OneAccuSystem.
- Voltage – 18 V.

HT2E242-C60:

- Voltage 18 V.
- Current 4A.
- Weight 0.56kg.
- Protections - overheating, overcharging, short circuit.
- Charging process indicator.
- Charging time 80 % of a 2 A battery - 30 min.
- Charging time 80 % of a 4 A battery - 60 min.
- Charging time 80 % of a 6 A battery - 90 min.

HT2E240-A40:

- Li-Ion technology.
- Voltage – 18 V.
- Capacity – 4.0 Ah.
- Weight – 0.67 kg.
- Protection against overheating, overcharging, short circuit.
- Charging level.
- EAN code – 5902801489785.

Technical data

			
HT2E249-B24CH	5902801490415	0	

Höbert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland

Producent/ Manufacturer/ Hersteller/ Произведено для:
PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków,
Polska/ Poland/ Polen/ Польша

Importer/ Импортёр:

HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska

Distributor:

ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón
308, 46021 Valencia, Spain

CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince
879, 720 00 Ostrava Hrabová