





CE

Power	<b>75 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>11625 lm (360°)</b>	Colour temperature	<b>4000 K</b>
Light colour	<b>Neutral white</b>	Beam angle	<b>40x110 °</b>
IK	<b>10</b>	Protection class	<b>IP66</b>




 User manual



 Declaration of Conformity

**Technical data:**

Product code	SLI048007NW_PW
Power	75 W
Nominal current	345 mA
Voltage	230 V
Energy consumption	75 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	11625 lm (360°)
Luminous flux**	11250 lm (360°)
Light efficiency	155 lm/W
Luminous intensity	9500 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	40x110 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Protection class	IP66
Colour	Black
Dimension (axbxc)	547x150x130 mm
For use	Outside/Inside
Assembly method	Suspended
Whether it should work in conditions other than normal?	Yes
Made in	PRC



\*Applies to the LED source used. \*\*Luminaire luminous flux