





CE

Power	150 W	Voltage	230 V
Luminous flux*	23250 lm (360°)	Colour temperature	4000 K
Light colour	Neutral white	Beam angle	60x90 °
IK	10	Protection class	IP66





 User manual



 Declaration of Conformity

Technical data:

Product code	SLI048008NW_PW
Power	150 W
Nominal current	665 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	23250 lm (360°)
Luminous flux**	22500 lm (360°)
Light efficiency	155 lm/W
Luminous intensity	22350 cd
Colour temperature	4000 K
Light colour	Neutral white
Beam angle	60x90 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Protection class	IP66
Colour	Black
Dimension (axbxc)	900x150x130 mm
For use	Outside/Inside
Assembly method	Suspended
Whether it should work in conditions other than normal?	Yes
Made in	PRC
Other	Zaw. 2 źródła św. o EEI D, Fi use=11625lm, P=75W ,



*Applies to the LED source used. **Luminaire luminous flux