


item number	dn outer Ø (mm)	thread	R (mm)	weight 1 pc (kg)	package (pcs)
<b>6116E_ECZ</b>	16	M16x1,5	55	0,11	15
<b>6120_ECZ</b>	20	M20x1,5	70	0,20	25
<b>6125_ECZ</b>	25	M25x1,5	115	0,28	25
<b>6132_ECZ</b>	32	M32x1,5	125	0,49	20
<b>6140_ECZ</b>	40	M40x1,5	140	0,72	15
<b>6150_ECZ</b>	50	M50x1,5	170	1,23	5
<b>6163_ECZ</b>	63	M63x1,5	210	1,72	3
<b>6116E_ZN_F</b>	16	M16x1,5	55	0,14	15
<b>6120_ZN_F</b>	20	M20x1,5	70	0,21	25
<b>6125_ZN_F</b>	25	M25x1,5	115	0,30	25
<b>6132_ZN_F</b>	32	M32x1,5	125	0,52	20
<b>6140_ZN_F</b>	40	M40x1,5	140	0,77	15
<b>6150_ZN_F</b>	50	M50x1,5	170	1,31	5
<b>6163_ZN_F</b>	63	M63x1,5	210	1,91	3



product description: Electrical wiring elbows are suitable for bending cable trays running through electrical wiring tubes with maintained functionality during fires by 90° horizontally.  
Steel couplings are mounted on elbows from one side.

surface finish: F - Hot Dip Galvanized, zinc-layer 50 - 100 µm  
EOZ - powder coating, black color RAL 9005

sales amount: á 1 pc

certification: EN 61 386-1 ed.2; IEC 61 386-1 ed.2

classification: ČSN 73 0895 P 90-R  
DIN 4102-12 E 90  
STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire.

Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1