



product description:

- designed for distribution system with voltage 400 V and with maximum current 16 A
- designed for mounting into hollow walls (eg. walls of plasterboard)
- inlet openings made of flexible material
- marked inputs for sealing cables and pipes in the flexible material (6x 6-10 mm, 2x 20-25 mm)
- air-tightness even with inserted cable or pipe
- suitable for low energy and passive houses
- prevents airflow through the installation
- mounting screws with plastic foot are fitted with a twin self-tapping thread for quick installation
- when mounting, it is not necessary to countersink the plasterboard edge
- possibility to insert screwless terminals
- IP protection is IP 30 (with the cover V 68 mounted)

material: PVC (Pb Free)

color: yellow

self-snuffing: yes, within 30 s

temperature resistance: -5 - +60 °C

flaming loop test: 850 °C

fire class for underlying material: A1-F

weight: 45 g

meets the requirements: EN 60 670-1

storage: ČSN 64 0090

KUL 68-45/LD2_NA - boxes fitted with screws for mounting into double wall and V 68 cover - package: 100 pcs in carton_EN

- accessories:**
- terminal plate S-66
 - screwless terminal plates TYP015, TYP016, TYP017, TYP018

- auxiliary tools:**
- saw-drill VPT 68
 - universal carrier VPTU