

item number	height H (mm)	length (mm)	thickness of metal sheet (mm)
<b>NPZ 50_S</b>	44	2000	0,8
<b>NPZ 100_S</b>	94	2000	0,8
<b>NPZ 50_F</b>	44	2000	0,8
<b>NPZ 100_F</b>	94	2000	0,8

product description: The partition is used to separate cables in cable trays.  
 The connection is performed using 2 pieces of the NSM 6X10 bolts per 1 meter of NPZ. The bolt head is inside the cable tray to protect the cables inside.  
 A bolt with a GMT surface finish is used for a tray with an F surface finish.

surface finish: S - Pre-Galvanized, zinc-layer 15 - 27 µm  
 F - Hot Dip Galvanized, zinc-layer 50 - 100 µm  
 EC - epoxy paint for indoor use - total paint, 60 µm

sales amount: á 2000 mm

meets the requirements: EN 61537:02

classification: ČSN 73 0895 P 90-R  
 DIN 4102-12 E 90  
 STN 92 0205 PS 90

Fire classification is depend on the specific conditions of the cable tray, detailed in the catalog Systems with maintained functionality in fire

Systems may be supplied with various surface finishes whereas the surface finish does not affect the determined maintained time of operability in fire.

storage: EN 60721-3-1

