



product description: rigid socket pipes are fireproof-tested  
 the pipes are intended for installation to the distribution of low voltage  
 possibility to install in places with risk of flammable gases and vapor – danger zone 2  
 possibility to install in places with explosive risk of dust – danger zone 22

material: PVC  
 color: light grey RAL 7035, white RAL 9003, black RAL 9005  
 self-snuffing: yes, within 30 s  
 temperature resistance: -25 - +60 °C  
 fire class for underlying material: A1-F  
 UV stable: no  
 mechanical resistance: 320 N / 5 cm  
 mechanical protection according to EN 50102: IK06  
 classification according to EN 61386-1 ed. 2: 22411  
 meets the requirements: EN 61386-1 ed.2:09, EN 61386-21:04, EN 50102  
 storage: ČSN 64 0090  
 length tolerance: ± 10 mm



recommendations: manufacturer recommends the assembling of plastic pipes at the temperature over 0 °C

accessories: elbows: 4116, 4120, 4125, 4132, 4140, 4150  
 connectors: 0216E, 0220, 0225, 0232, 0240, 0250, 0263  
 clamps: 5316E, 5320, 5325, 5332, 5340, 5350, 5363

chemical resistance: YES: amoniak 25%, distilled water, ethanol 50%, sodium hydroxide 60%, hydrofluoric acid 40%, acetic acid 5%, sulfuric acid 96%, medicinal oil, methanol, olive oil, petroleum, hydrogen peroxide 20%, transformer oil, sodium carbonate  
 NO: aceton, benzen, chlorinated hydrocarbons, tetrachlorocarbon

item number	dn outer Ø (mm)	di min. inner Ø (mm)	length (m)	weight (kg/m)	package	color
<b>1516E_FA</b>	16	13,7	3	0,07	30	black RAL 9005
<b>1516E_HA</b>	16	13,7	3	0,07	30	white RAL 9003
<b>1516E_KA</b>	16	13,7	3	0,07	30	light gray RAL 7035
<b>1516E_KC</b>	16	13,7	2	0,07	20	light gray RAL 7035
<b>1520_FA</b>	20	17,4	3	0,10	30	black RAL 9005
<b>1520_HA</b>	20	17,4	3	0,10	30	white RAL 9003
<b>1520_KA</b>	20	17,4	3	0,10	30	light gray RAL 7035
<b>1520_KC</b>	20	17,4	2	0,10	20	light gray RAL 7035
<b>1525_FA</b>	25	22,1	3	0,14	30	black RAL 9005
<b>1525_HA</b>	25	22,1	3	0,14	30	white RAL 9003
<b>1525_KA</b>	25	22,1	3	0,14	30	light gray RAL 7035
<b>1525_KC</b>	25	22,1	2	0,14	20	light gray RAL 7035
<b>1532_FA</b>	32	28,6	3	0,18	30	black RAL 9005
<b>1532_HA</b>	32	28,6	3	0,18	30	white RAL 9003
<b>1532_KA</b>	32	28,6	3	0,18	30	light gray RAL 7035
<b>1532_KC</b>	32	28,6	2	0,18	20	light gray RAL 7035
<b>1540_HA</b>	40	36,6	3	0,25	30	white RAL 9003
<b>1540_KA</b>	40	36,6	3	0,25	30	light gray RAL 7035
<b>1540_KC</b>	40	36,6	2	0,25	20	light gray RAL 7035
<b>1550_HA</b>	50	45,9	3	0,37	30	white RAL 9003
<b>1550_KA</b>	50	45,9	3	0,37	30	light gray RAL 7035
<b>1550_KC</b>	50	45,9	2	0,37	20	light gray RAL 7035
<b>1563_HA</b>	63	58,4	3	0,52	15	white RAL 9003
<b>1563_KA</b>	63	58,4	3	0,52	15	light gray RAL 7035