

ONTEC R M2 302 M ST W

TM-OR.M2STM300W



No: 04A23



No: 4410/2021
Valid until:
04.09.2026



No: 88-128814
Valid until:
24.06.2025



No:
B_BK_60212_0267
Valid until:
30.06.2026



No: 04A23





No: 2247418.02-
UAE
Valid until:
24.06.2025



No: 04A23



Producer	TM Technologie
Category	emergency luminaires
Application	anti-panic lighting
Family	ONTEC R
Colour/Colour - RAL	white , RAL9003
Version	standard
Operating mode	M
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Colour structure	matte , satin, smooth
Installation method*	surface, flush-mounted, wall, ceiling
Luminous flux emergency	288 lm
Light source	LED
Maximum light power	2 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	10 °C
Maximum temperature	35 °C
Battery	LiFePO4/C 6.4V 1.5Ah
Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	130 mm x 31 mm x 130 mm



h	a	b	c	d
2,5	3,5	8,5	3,5	8,5
3	4	9,5	4	9,5
4	4,5	12	4,5	12
5	5	14	5	14
6	5	15,5	5	15,5
7	4	17	4	17
8	4	17,5	4	17,5
9	4	18	4	18
10	3	19	3	19

* Some of mounting methods are possible only with additional accessory dedicated for that product.