

# ONTEC R M2 302 M AT W TM-OR.M2ATM300W



No: 04A23



No: 4410/2021  
Valid until:  
04.09.2026



No: 88-128814  
Valid until:  
24.06.2025



No:  
B\_BK\_60212\_0267  
Valid until:  
30.06.2026



No: 04A23





No: 2247418.02-  
UAE  
Valid until:  
24.06.2025



No: 04A23



Producer	<b>TM Technologie</b>
Category	<b>emergency luminaires</b>
Application	<b>anti-panic lighting</b>
Family	<b>ONTEC R</b>
Colour/Colour - RAL	<b>white , RAL9003</b>
Version	<b>autotest</b>
Operating mode	<b>M</b>
Duration time	<b>3 h</b>
Protection degree	<b>IP20</b>
Impact protection degree	<b>IK03</b>
Appliance classes	<b>II</b>
Material	<b>plastic</b>
Colour structure	<b>matte , satin, smooth</b>
Installation method*	<b>surface, flush-mounted, wall, ceiling</b>
Luminous flux emergency	<b>288 lm</b>
Light source	<b>LED</b>
Maximum light power	<b>2 W</b>
LED lifetime	<b>50000 h</b>
Colour temperature	<b>5700 K</b>
Minimum temperature	<b>10 °C</b>
Maximum temperature	<b>35 °C</b>
Battery	<b>LiFePO4/C 6.4V 1.5Ah</b>
Warranty (body, electronics, light source)	<b>36 months</b>
Net dimensions <b>L x W x H</b> [±2 mm]	<b>130 mm x 31 mm x 130 mm</b>



h	a	b	c	d
2,5	3,5	8,5	3,5	8,5
3	4	9,5	4	9,5
4	4,5	12	4,5	12
5	5	14	5	14
6	5	15,5	5	15,5
7	4	17	4	17
8	4	17,5	4	17,5
9	4	18	4	18
10	3	19	3	19

\* Some of mounting methods are possible only with additional accessory dedicated for that product.