

ONTEC S20 M1U 60 NM ST W IP65 TM-S2.MUSTN160W



No: 16A23



No: 4302/2021
Valid until:
15.04.2026



No: 88-129369
Valid until:
24.06.2025



No:
B_BK_60212_0507
Valid until:
18.12.2025



No: 16A23



No: 2276393.01-
UAE
Valid until:
24.07.2025









No: 16A23



Producer **TM Technologie**
Category **emergency luminaires**
Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S20**
Colour/Colour - RAL **white , RAL9003**
Version **standard**
Operating mode **NM**
Duration time **1 h**
Protection degree **IP65**
Impact protection degree **IK08**
Appliance classes **II**
Material **plastic**
Colour structure **smooth, gloss**
Installation method* **surface, flush-mounted, suspended, wall, ceiling**
Adapted to use a pictogram **yes**
Luminous flux **>2 cd/m²**
Luminous flux emergency **125 lm**
Light source **LED**
Maximum light power **0.9 W**
LED lifetime **50000 h**
Colour temperature **5700 K**
Minimum temperature **5 °C**
Maximum temperature **40 °C**
Battery **LiFePO4/C 3.2V 1.5Ah**
Warranty (body, electronics, light source) **24 months**
Net dimensions **L x W x H [±2 mm]** **227 mm x 40 mm x 120 mm**



2,5	3,0	7,0	3,0	7,0
3,0	3,0	8,0	3,0	8,0
4,0	3,0	9,5	3,0	9,5
5,0	3,5	10,5	3,5	10,5
6,0	3,5	11,5	3,5	11,5
7,0	3,5	12,0	3,5	12,0
8,0	2,5	13,0	2,5	13,0
9,0	2,0	13,5	2,0	13,5
10,0	1,5	13,5	1,5	13,5

* Some of mounting methods are possible only with additional accessory dedicated for that product.