

S20 M1X 60/180 M/NM AT W IP65 TM-S2.MXATX060W



No: 16A23



No: 4302/2021
Valid until:
15.04.2026



No: 88-129369
Valid until:
24.06.2025



No:
B_BK_60212_0507
Valid until:
18.12.2025



No: 16A23



No: 2276393.01-
UAE
Valid until:
24.07.2025






No: 16A23



Producer **TM Technologie**
Category **emergency luminaires**
Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S20**
Colour/Colour - RAL **white , RAL9003**
Version **autotest**
Operating mode **M/NM**
Duration time **1/3 h**
Protection degree **IP65**
Impact protection degree **IK08**
Appliance classes **II**
Material **plastic**
Colour structure **smooth, gloss**
Installation method* **surface, flush-mounted, suspended, wall, ceiling**
Adapted to use a pictogram **yes**
Luminous flux **>2 cd/m²**
Luminous flux emergency **371(1h);154(3h) lm**
Light source **LED**
Maximum light power **3 W**
LED lifetime **50000 h**
Colour temperature **5700 K**
Minimum temperature **5 °C**
Maximum temperature **40 °C**
Battery **LiFePO4/C 3.2V 1.5Ah**
Warranty (body, electronics, light source) **36 months**
Net dimensions **L x W x H [±2 mm] 227 mm x 40 mm x 120 mm**





*60				
2,5	3,5	8	3,5	8
3	3,5	9,5	3,5	9,5
4	4,5	11,5	4,5	11,5
5	5	13	5	13
6	5	15	5	15
7	5	16,5	5	16,5
8	5,5	18	5,5	18
9	5,5	19	5,5	19
10	5,5	20	5,5	20
*180				
2,5	3	7	3	7
3	3,5	8	3,5	8
4	4	9,5	4	9,5
5	4	11	4	11
6	3,5	12,5	3,5	12,5
7	3,5	13,5	3,5	13,5
8	3,5	14	3,5	14
9	3	14,5	3	14,5
10	2	15	2	15