

# ONTEC S20 M2 180 M ST W IP65 TM-S2.M2STM360W



No: 16A23



No: 4302/2021  
Valid until:  
15.04.2026



No: 88-129369  
Valid until:  
24.06.2025



No:  
B\_BK\_60212\_0507  
Valid until:  
18.12.2025



No: 16A23



No: 2276393.01-  
UAE  
Valid until:  
24.07.2025









No: 16A23



Producer **TM Technologie**  
Category **emergency luminaires**  
Application **anti-panic lighting, evacuation route direction**

Family **ONTEC S20**  
Colour/Colour - RAL **white , RAL9003**  
Version **standard**  
Operating mode **M**  
Duration time **3 h**  
Protection degree **IP65**  
Impact protection degree **IK08**  
Appliance classes **II**  
Material **plastic**  
Colour structure **smooth, gloss**  
Installation method\* **surface, flush-mounted, suspended, wall, ceiling**  
Adapted to use a pictogram **yes**  
Luminous flux **>2 cd/m<sup>2</sup>**  
Luminous flux emergency **309 lm**  
Light source **LED**  
Maximum light power **2.5 W**  
LED lifetime **50000 h**  
Colour temperature **5700 K**  
Minimum temperature **5 °C**  
Maximum temperature **40 °C**  
Battery **LiFePO4/C 2x3.2V 1.5Ah**  
Warranty (body, electronics, light source) **24 months**  
Net dimensions **L x W x H [±2 mm]** **227 mm x 40 mm x 120 mm**



2,5	3,5	8,0	3,5	8,0
3,0	3,5	9,0	3,5	9,0
4,0	4,5	11,0	4,5	11,0
5,0	5,0	12,5	5,0	12,5
6,0	5,0	14,5	5,0	14,5
7,0	5,0	16,0	5,0	16,0
8,0	5,5	17,0	5,5	17,0
9,0	5,5	18,0	5,5	18,0
10,0	5,0	19,0	5,0	19,0

\* Some of mounting methods are possible only with additional accessory dedicated for that product.