

ONTEC C M1 60 NM ST B

TM-OC.M1STN600B



No: 01A23



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463
Valid until:
25.05.2026



No:
B_BK_60212_0267
Valid until:
30.06.2026



No: 01A23





No: 2247418.02-
UAE
Valid until:
24.06.2025



No: 01A23



Producer	TM Technologie
Category	emergency luminaires
Application	anti-panic lighting
Family	ONTEC C
Colour/Colour - RAL	black , RAL9005
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Colour structure	matte , satin, smooth
Installation method*	flush-mounted, ceiling
Luminous flux emergency	338 lm
Light source	LED
Maximum light power	3 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	10 °C
Maximum temperature	35 °C
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty (body, electronics, light source)	24 months
Net dimensions H x Ø [±2 mm]	14 mm x 90 mm



h	a	b	c	d
2,5	3,5	8,0	3,5	8,0
3,0	4,0	9,0	4,0	9,0
4,0	5,0	11,0	5,0	11,0
5,0	5,5	13,0	5,5	13,0
6,0	5,5	15,0	5,5	15,0
7,0	6,0	16,5	6,0	16,5
8,0	6,0	18,0	6,0	18,0
9,0	5,5	19,0	5,5	19,0
10,0	5,0	20,0	5,0	20,0

* Some of mounting methods are possible only with additional accessory dedicated for that product.