

ONTEC D M1 60 NM AT B

TM-OD.M1ATN600B



No: 01A23



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463
Valid until:
24.06.2025



No:
B_BK_60212_0267
Valid until:
30.06.2026



No: 01A23





No: 2247418.02-
UAE
Valid until:
24.06.2025



No: 01A23



| | |
|--|-------------------------------|
| Producer | TM Technologie |
| Category | emergency luminaires |
| Application | anti-panic lighting |
| Family | ONTEC D |
| Colour/Colour - RAL | black , RAL9005 |
| Version | autotest |
| Operating mode | NM |
| Duration time | 1 h |
| Protection degree | IP20 |
| Impact protection degree | IK03 |
| Appliance classes | II |
| Material | plastic |
| Colour structure | matte , satin, smooth |
| Installation method* | flush-mounted, ceiling |
| Luminous flux emergency | 338 lm |
| Light source | LED |
| Maximum light power | 3 W |
| LED lifetime | 50000 h |
| Colour temperature | 5700 K |
| Minimum temperature | 10 °C |
| Maximum temperature | 35 °C |
| Battery | LiFePO4/C 3.2V 1.5Ah |
| Warranty (body, electronics, light source) | 36 months |
| Net dimensions L x W x H [±2 mm] | 90 mm x 90 mm x 14 mm |



| | | | | |
|------|-----|------|-----|------|
| | | | | |
| 2,5 | 3,5 | 8,0 | 3,5 | 8,0 |
| 3,0 | 4,0 | 9,0 | 4,0 | 9,0 |
| 4,0 | 5,0 | 11,0 | 5,0 | 11,0 |
| 5,0 | 5,5 | 13,0 | 5,5 | 13,0 |
| 6,0 | 5,5 | 15,0 | 5,5 | 15,0 |
| 7,0 | 6,0 | 16,5 | 6,0 | 16,5 |
| 8,0 | 6,0 | 18,0 | 6,0 | 18,0 |
| 9,0 | 5,5 | 19,0 | 5,5 | 19,0 |
| 10,0 | 5,0 | 20,0 | 5,0 | 20,0 |

* Some of mounting methods are possible only with additional accessory dedicated for that product.