

ONTEC D M1 180 NM AT B TM-OD.M1ATN800B



No: 01A23



No: 4397/2021
Valid until:
11.09.2026



No: 88-128463
Valid until:
24.06.2025



No:
B_BK_60212_0267
Valid until:
30.06.2026



No: 01A23





No: 2247418.02-
UAE
Valid until:
24.06.2025



No: 01A23



Producer	TM Technologie
Category	emergency luminaires
Application	anti-panic lighting
Family	ONTEC D
Colour/Colour - RAL	black , RAL9005
Version	autotest
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Colour structure	matte , satin, smooth
Installation method*	flush-mounted, ceiling
Luminous flux emergency	167 lm
Light source	LED
Maximum light power	3 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	10 °C
Maximum temperature	35 °C
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	90 mm x 90 mm x 14 mm



2,5	3,0	7,5	3,0	7,5
3,0	3,5	8,5	3,5	8,5
4,0	4,0	10,0	4,0	10,0
5,0	4,5	11,5	4,5	11,5
6,0	4,0	13,0	4,0	13,0
7,0	3,5	14,0	3,5	14,0
8,0	2,5	15,0	2,5	15,0
9,0	2,5	15,0	2,5	15,0
10,0	2,0	15,0	2,0	15,0

* Some of mounting methods are possible only with additional accessory dedicated for that product.