

ONTEC R M1 60 NM ST B

TM-OR.M1STN600B



No: 04A23



No: 4410/2021
Valid until:
04.09.2026



No: 88-128814
Valid until:
24.06.2025



No:
B_BK_60212_0267
Valid until:
30.06.2026




No: 04A23





No: 2247418.02-
UAE
Valid until:
24.06.2025



No: 04A23



Producer	TM Technologie
Category	emergency luminaires
Application	anti-panic lighting
Family	ONTEC R
Colour/Colour - RAL	black , RAL9005
Version	standard
Operating mode	NM
Duration time	1 h
Protection degree	IP20
Impact protection degree	IK03
Appliance classes	II
Material	plastic
Colour structure	matte , satin, smooth
Installation method*	surface, flush-mounted, wall, ceiling
Luminous flux emergency	360 lm
Light source	LED
Maximum light power	2 W
LED lifetime	50000 h
Colour temperature	5700 K
Minimum temperature	10 °C
Maximum temperature	35 °C
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty (body, electronics, light source)	24 months
Net dimensions L x W x H [±2 mm]	130 mm x 31 mm x 130 mm



h	a	b	c	d
2,5	4,0	8,5	4,0	8,5
3,0	4,0	10,0	4,0	10,0
4,0	5,0	12,5	5,0	12,5
5,0	5,5	14,5	5,5	14,5
6,0	5,5	16,5	5,5	16,5
7,0	5,0	18,0	5,0	18,0
8,0	5,0	19,0	5,0	19,0
9,0	4,5	20,0	4,5	20,0
10,0	4,0	20,5	4,0	20,5

* Some of mounting methods are possible only with additional accessory dedicated for that product.