

ONTEC G E1E 180 NM AT W TM-OG.EEATN800W



No: 03A23



No: 4420/2021
Valid until:
05.09.2026



No: 88-128652
Valid until:
24.06.2025



No:
B_BK_60212_0267
Valid until:
30.06.2026



No: 03A23



No: 2247418.02-
UAE
Valid until:
24.06.2025



No: 03A23



Producer	TM Technologie
Category	emergency luminaires
Application	evacuation route direction
Family	ONTEC G
Colour/Colour - RAL	white , RAL9003
Colour structure	matte , satin, smooth
Version	autotest
Operating mode	NM
Duration time	3 h
Protection degree	IP20
Impact protection degree	IK05
Appliance classes	II
Material	plastic
Installation method*	surface, flush-mounted, suspended, wall, ceiling
Adapted to use a pictogram	yes
Pictogram included	yes
Pictogram dimensions	125x125 mm
Evacuation sign dimensions	250x125 mm
Pictogram type	foil
Graphic number	K6
Pictogram logo	TM Technologie
Luminous flux	>300 cd/m²
Colour temperature	5700 K
Light source	LED
Maximum light power	0.9 W
LED lifetime	50000 h
Minimum temperature	10 °C
Maximum temperature	35 °C
Battery	LiFePO4/C 3.2V 1.5Ah
Warranty (body, electronics, light source)	36 months
Net dimensions L x W x H [±2 mm]	251 mm x 29 mm x 198 mm

